



Rocky Enterprise Linux 9.2 Manual Pages on command 'WWW::RobotRules::AnyDBM_File.3pm'

C:\>man WWW::RobotRules::AnyDBM_File.3pm

WWW::RobotRules::AnyDBM_FileUser)Contributed Perl DocumenWWW::RobotRules::AnyDBM_File(3pm)

NAME

WWW::RobotRules::AnyDBM_File - Persistent RobotRules

SYNOPSIS

```
require WWW::RobotRules::AnyDBM_File;
require LWP::RobotUA;

# Create a robot useragent that uses a diskcaching RobotRules
my $rules = WWW::RobotRules::AnyDBM_File->new( 'my-robot/1.0', 'cachefile' );
my $ua = WWW::RobotUA->new( 'my-robot/1.0', 'me@foo.com', $rules );

# Then just use $ua as usual
$res = $ua->request($req);
```

DESCRIPTION

This is a subclass of WWW::RobotRules that uses the AnyDBM_File package to implement persistent diskcaching of robots.txt and host visit information.

The constructor (the new() method) takes an extra argument specifying the name of the DBM file to use. If the DBM file already exists, then you can specify undef as

agent name as the name can be obtained from the DBM database.

SEE ALSO

WWW::RobotRules, LWP::RobotUA

AUTHORS

Hakan Ardo <hakan@munin.ub2.lu.se>, Gisle Aas <aas@sn.no>

perl v5.26.1

2018-04-14

WWW::RobotRules::AnyDBM_File(3pm)