



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'X11::Keysyms.3pm'***

**C:\>man X11::Keysyms.3pm**

Keysyms(3pm)            User Contributed Perl Documentation            Keysyms(3pm)

### NAME

X11::Keysyms - Perl module for names of X11 keysyms

### SYNOPSIS

```
use X11::Keysyms '%Keysyms', qw(MISCELLANY XKB_KEYS LATIN1);

%Keysyms_name = reverse %Keysyms;

$ks = $Keysyms{'BackSpace'};

$name = $Keysyms_name{$ks};
```

### DESCRIPTION

This module exports a hash mapping the names of X11 keysyms, such as 'A' or 'Linefeed' or 'Hangul\_J\_YeorinHieuh', onto the numbers that represent them. The first argument to 'use' is the name of the variable the hash should be exported into, and the rest are names of subsets of the keysyms to export: one or more of 'MISCELLANY', 'XKB\_KEYS', '3270', 'LATIN1', 'LATIN2', 'LATIN3', 'LATIN4', 'KATAKANA', 'ARABIC', 'CYRILLIC', 'GREEK', 'TECHNICAL', 'SPECIAL', 'PUBLISHING', 'APL', 'HEBREW', 'THAI', 'KOREAN'.

If this list is omitted, the list

```
'MISCELLANY', 'XKB_KEYS', 'LATIN1', 'LATIN2', 'LATIN3',
'LATIN4', 'GREEK'
```

is used.

AUTHOR

This module was generated semi-automatically by Stephen McCamant  
(<SMCCAM@cpan.org>) from the header file 'X11/keysymdef.h', distributed by the X  
Consortium.

SEE ALSO

perl(1), X11::Protocol, X Window System Protocol (X Version 11).

perl v5.20.2

2003-01-27

Keysyms(3pm)