



Rocky Enterprise Linux 9.2 Manual Pages on command 'X11::Protocol::Ext::XC_MISC.3pm'

C:\>man X11::Protocol::Ext::XC_MISC.3pm

Protocol::Ext::XC_MISC(3pm) User Contributed Perl DocumentationProtocol::Ext::XC_MISC(3pm)

NAME

X11::Protocol::Ext::XC_MISC - Perl module for the X11 Protocol XC-MISC Extension

SYNOPSIS

```
use X11::Protocol;  
  
$x = X11::Protocol->new();  
  
$x->init_extension('XC-MISC');
```

DESCRIPTION

This module is used by the programmer to pre-acquire large numbers of X resource IDs to be used with the X11::Protocol module.

If supported by the server, X11::Protocol will load this module automatically when additional resource IDs are needed via the standard `new_rsrc()` interface. However, if you anticipate that a program will run for a long time and allocate many resources, it would be a good idea to initialize the extension at startup to verify its existence.

REQUESTS

This extension adds three requests, called as shown below:

```
$x->XCMiscGetVersion => ($major, $minor)  
  
$x->XCMiscGetXIDRange => ($start_id, $count)  
  
$x->XCMiscGetXIDList($count) => ($count, @ids)
```

AUTHOR

Jay Kominek <jay.kominek@colorado.edu>.

SEE ALSO

perl(1), X11::Protocol, XC-MISC Extension (X Consortium Standard).

perl v5.20.2

2003-05-11

Protocol::Ext::XC_MISC(3pm)