



Rocky Enterprise Linux 9.2 Manual Pages on command 'XtCallActionProc.3'

C:\>man XtCallActionProc.3

XtCallActionProc(3) XT FUNCTIONS XtCallActionProc(3)

NAME

XtCallActionProc - invoke an action procedure directly

SYNTAX

```
void XtCallActionProc(Widget widget, String action, XEvent* event, String* params,  
                      Cardinal num_params);
```

ARGUMENTS

widget Specifies the widget in which the action is to be invoked. Must be of
 class core of any subclass thereof.

action Specifies the name of the action routine.

event Specifies the contents of the event passed to the action routine.

params Specifies the contents of the params passed to the action routine.

num_params

 Specifies the num of entries in params.

DESCRIPTION

XtCallActionProc searches for the named action routine in the same manner and order as translation tables are bound. If found, the action routine is invoked with the specified widget, event pointer, and parameters. It is the responsibility of the caller to ensure that the contents of event, params, and num_params arguments are appropriate for the specified routine, and if necessary, that the specified widget is realized or sensitive. If the named action routine cannot be found, XtCall?

ActionProc generates a warning message and returns.

SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.1.5

XtCallActionProc(3)