



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtDisownSelection.3'***

**C:\>man XtDisownSelection.3**

XtOwnSelection(3)                    XT FUNCTIONS                    XtOwnSelection(3)

### NAME

XtOwnSelection, XtOwnSelectionIncremental, XtDisownSelection - set selection owner

### SYNTAX

```
Boolean XtOwnSelection(Widget w, Atom selection, Time time, XtConvertSelectionProc
    convert_proc, XtLoseSelectionProc lose_selection, XtSelectionDoneProc
    done_proc);
```

```
Boolean XtOwnSelectionIncremental(Widget w, Atom selection, Time time, XtConvertSe?
    lectionIncrProc convert_callback, XtLoseSelectionIncrProc lose_callback,
    XtSelectionDoneIncrProc done_callback, XtCancelConvertSelectionProc can?
    cel_callback, XtPointer client_data);
```

```
void XtDisownSelection(Widget w, Atom selection, Time time);
```

### ARGUMENTS

convert\_proc

Specifies the procedure that is to be called whenever someone requests the current value of the selection.

`done_proc` Specifies the procedure that is called after the requestor has received the selection or NULL if the owner is not interested in being called back.

`lose_selection`

Specifies the procedure that is to be called whenever the widget has lost selection ownership or NULL if the owner is not interested in being called back.

`selection` Specifies an atom that describes the type of the selection (for example, `XA_PRIMARY`, `XA_SECONDARY`, or `XA_CLIPBOARD`).

`time` Specifies the timestamp that indicates when the selection ownership should commence or is to be relinquished.

`w` Specifies the widget that wishes to become the owner or to relinquish ownership.

## DESCRIPTION

The `XtOwnSelection` function informs the Intrinsic selection mechanism that a widget believes it owns a selection. It returns `True` if the widget has successfully become the owner and `False` otherwise. The widget may fail to become the owner if some other widget has asserted ownership at a time later than this widget. Note that widgets can lose selection ownership either because someone else asserted later ownership of the selection or because the widget voluntarily gave up ownership of the selection. Also note that the `lose_selection` procedure is not called if the widget fails to obtain selection ownership in the first place.

The `XtOwnSelectionIncremental` procedure informs the Intrinsic incremental selection mechanism that the specified widget wishes to own the selection. It returns `True` if the specified widget successfully becomes the selection owner or `False` otherwise. For more information about selection, target, and time, see Section 2.6 of the Inter-Client Communication Conventions Manual.

A widget that becomes the selection owner using `XtOwnSelectionIncremental` may use `XtDisownSelection` to relinquish selection ownership.

The `XtDisownSelection` function informs the Intrinsic selection mechanism that the specified widget is to lose ownership of the selection. If the widget does not currently own the selection either because it lost the selection or because it never had the selection to begin with, `XtDisownSelection` does nothing.

After a widget has called `XtDisownSelection`, its convert procedure is not called even if a request arrives later with a timestamp during the period that this widget owned the selection. However, its done procedure will be called if a conversion that started before the call to `XtDisownSelection` finishes after the call to `XtDisownSelection`.

#### SEE ALSO

`XtAppGetSelectionTimeout(3)`, `XtGetSelectionValue(3)`

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface