



Rocky Enterprise Linux 9.2 Manual Pages on command 'XtErrorMsg.3'

C:\>man XtErrorMsg.3

XtErrorMsg(3) XT COMPATIBILITY FUNCTIONS XtErrorMsg(3)

NAME

XtErrorMsg, XtSetErrorMsgHandler, XtWarningMsg, XtSetWarningMsgHandler - high-level error handlers

SYNTAX

```
void XtErrorMsg(String name, String type, String class, String default, String
    *params, Cardinal *num_params);
```

```
void XtSetErrorMsgHandler(XtErrorMsgHandler msg_handler);
```

```
void XtSetWarningMsgHandler(XtErrorMsgHandler msg_handler);
```

```
void XtWarningMsg(String name, String type, String class, String default, String
    *params, Cardinal *num_params);
```

ARGUMENTS

class Specifies the resource class.

default Specifies the default message to use.

name Specifies the general kind of error.

type Specifies the detailed name of the error.

msg_handler

Specifies the new fatal error procedure, which should not return or the nonfatal error procedure, which usually returns.

num_params

Specifies the number of values in the parameter list.

params Specifies a pointer to a list of values to be stored in the message.

DESCRIPTION

The XtErrorMsg function has been superceded by XtAppErrorMsg.

The XtSetErrorMsgHandler function has been superceded by XtAppSetErrorMsgHandler.

The XtSetWarningMsgHandler function has been superceded by XtAppSetWarningMsgHandler.

The XtWarningMsg function has been superceded by XtAppWarningMsg.

SEE ALSO

XtAppErrorMsg(3)

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface