



Rocky Enterprise Linux 9.2 Manual Pages on command 'XtGetActionKeysym.3'

C:\>man XtGetActionKeysym.3

XtGetActionKeysym(3) XT FUNCTIONS XtGetActionKeysym(3)

NAME

XtGetActionKeysym - obtain corresponding keysym

SYNTAX

KeySym XtGetActionKeysym(XEvent* event, Modifiers* modifiers_return);

ARGUMENTS

event Specifies the event pointer passed to the action procedure by the Intrin?
sics.

modifiers_return

Returns the modifiers that caused the match, if non-NULL.

DESCRIPTION

If XtGetActionKeysym is called after an action procedure has been invoked by the
Intrinsics and before that action procedure returns, and if the event pointer has
the same value as the event pointer passed to that action routine, and if the event
is a KeyPress or KeyRelease event, then XtGetActionKeysym returns the KeySym that
matched the final event specification in the translation table and, if modi?

fiers_return is non-NULL, the modifier state actually used to generate this KeySym;

otherwise, if the event is a KeyPress or KeyRelease event, then XtGetActionKeysym calls XtTranslateKeycode and returns the results; else it returns NoSymbol and does not examine modifiers_return.

SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.1.5

XtGetActionKeysym(3)