



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtGetSelectionRequest.3'***

**C:~>man XtGetSelectionRequest.3**

XtGetSelectionRequest(3)      XT FUNCTIONS      XtGetSelectionRequest(3)

### NAME

XtGetSelectionRequest - retrieve the event that triggered the XtConvertSelection?

Proc

### SYNTAX

```
XSelectionRequestEvent* XtGetSelectionRequest(Widget w, Atom selection, XtRequestId  
request_id);
```

### ARGUMENTS

w      Specifies the widget.

selection Specifies the selection being processed.

request\_id

Specifies the requestor id in the case of incremental selections, or NULL  
in the case of atomic transfers.

### DESCRIPTION

XtGetSelectionRequest may only be called from within an XtConvertSelectionProc procedure and returns a pointer to the SelectionRequest event that caused the conversion.

sion procedure to be invoked. Request\_id specifies a unique id for the individual request in the case that multiple incremental transfers are outstanding. For atomic transfers, request\_id must be specified as NULL. If no SelectionRequest event is being processed for the specified widget, selection, and request\_id, XtGetSelectionRequest returns NULL.

#### SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.1.5

XtGetSelectionRequest(3)