



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtGetSubresources.3'***

**C:\>man XtGetSubresources.3**

XtGetSubresources(3)            XT FUNCTIONS            XtGetSubresources(3)

### NAME

XtGetSubresources, XtVaGetSubresources - obtain subresources

### SYNTAX

```
void XtGetSubresources(Widget w, XtPointer base, String name, String class, XtRe?
    sourceList resources, Cardinal num_resources, ArgList args, Cardinal
    num_args);
```

```
void XtVaGetSubresources(Widget w, XtPointer base, String name, String class, XtRe?
    sourceList resources, Cardinal num_resources);
```

### ARGUMENTS

**args**     Specifies the argument list to override resources obtained from the re?  
          source database.

**base**     Specifies the base address of the subpart data structure where the re?  
          sources should be written.

**class**    Specifies the class of the subpart.

name Specifies the name of the subpart.

num\_args Specifies the number of arguments in the argument list.

num\_resources

Specifies the number of resources in the resource list.

resources Specifies the resource list for the subpart.

w Specifies the widget that wants resources for a subpart or that identifies the resource database to search.

... Specifies the variable arguments to override resources obtained from the resource database.

## DESCRIPTION

The `XtGetSubresources` function constructs a name/class list from the application name/class, the name/classes of all its ancestors, and the widget itself. Then, it appends to this list the name/class pair passed in. The resources are fetched from the argument list, the resource database, or the default values in the resource list. Then, they are copied into the subpart record. If `args` is `NULL`, `num_args` must be zero. However, if `num_args` is zero, the argument list is not referenced.

## SEE ALSO

`XtGetApplicationResources`, `XtVaGetApplicationResources`

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface