



Rocky Enterprise Linux 9.2 Manual Pages on command 'XtSetKeyboardFocus.3'

C:\>man XtSetKeyboardFocus.3

XtSetKeyboardFocus(3) XT FUNCTIONS XtSetKeyboardFocus(3)

NAME

XtSetKeyboardFocus - focus events on a child widget

SYNTAX

XtSetKeyboardFocus(Widget subtree, Widget descendant);

ARGUMENTS

subtree Specifies either the widget in the subtree structure which is to receive the keyboard event, or None. Note that it is not an error to specify None when no input focus was previously set.

descendant

Specifies the widget for which the keyboard focus is to be set.

DESCRIPTION

If a future KeyPress or KeyRelease event occurs within the specified subtree, XtSetKeyboardFocus causes XtDispatchEvent to remap and send the event to the specified descendant widget.

When there is no modal cascade, keyboard events can occur within a widget W in one

of three ways:

? W has the X input focus.

? W has the keyboard focus of one of its ancestors, and the event occurs within the ancestor or one of the ancestor's descendants.

? No ancestor of W has a descendant within the keyboard focus, and the pointer is within W.

When there is a modal cascade, a widget W receives keyboard events if an ancestor of W is in the active subset of the modal cascade and one or more of the previous conditions is True.

When subtree or one of its descendants acquires the X input focus or the pointer moves into the subtree such that keyboard events would now be delivered to subtree, a FocusIn event is generated for the descendant if FocusNotify events have been selected by the descendant. Similarly, when W loses the X input focus or the keyboard focus for one of its ancestors, a FocusOut event is generated for descendant if FocusNotify events have been selected by the descendant.

SEE ALSO

XtCallAcceptFocus(3)

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.1.5

XtSetKeyboardFocus(3)