



Rocky Enterprise Linux 9.2 Manual Pages on command 'XtSetWMColormapWindows.3'

C:\>man XtSetWMColormapWindows.3

XtSetWMColormapWindows(3) XT FUNCTIONS XtSetWMColormapWindows(3)

NAME

XtSetWMColormapWindows - Set the value of the WM_COLORMAP_WINDOWS property

SYNTAX

```
void XtSetWMColormapWindows(Widget widget, Widget* list, Cardinal count);
```

ARGUMENTS

widget Specifies the widget on whose window the WM_COLORMAP_WINDOWS property will be stored. Must be of class Core or any subclass thereof.

list Specifies a list of widgets whose windows are potentially to be listed in the WM_COLORMAP_WINDOWS property.

count Specifies the number of widgets in list.

DESCRIPTION

XtSetWMColormapWindows returns immediately if widget is not realized or if count is zero. Otherwise, XtSetWMColormapWindows constructs an ordered list of windows by examining each widget in list in turn and ignoring the widget if it is not realized, or adding the widget's window to the window list if the widget is realized

and its colormap resource is different from the colormap resources of all widgets whose windows are already on the window list.

Finally, `XtSetWMColormapWindows` stores the resulting window list in the `WM_COLORMAP_WINDOWS` property on the specified widget's window.

SEE ALSO

[X Toolkit Intrinsics - C Language Interface](#)

[Xlib - C Language X Interface](#)

X Version 11

libXt 1.1.5

`XtSetWMColormapWindows(3)`