



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'a2enconf.8'***

**C:\>man a2enconf.8**

A2ENCONF(8)                      System Manager's Manual                      A2ENCONF(8)

### NAME

a2enconf, a2disconf - enable or disable an apache2 configuration file

### SYNOPSIS

a2enconf [ [-q|--quiet] configuration]

a2disconf [ [-q|--quiet] configuration]

### DESCRIPTION

This manual page documents briefly the a2enconf and a2disconf commands.

a2enconf is a script that enables the specified configuration file within the apache2 configuration. It does this by creating symlinks within /etc/apache2/conf-enabled. Likewise, a2disconf disables a specific configuration part by removing those symlinks. It is not an error to enable a configuration which is already enabled, or to disable one which is already disabled.

Note that many configuration file may have a dependency to specific modules. Unlike module dependencies, these are not resolved automatically. Configuration fragments stored in the conf-available directory are considered non-essential or being installed and managed by reverse dependencies (e.g. web scripts).

### OPTIONS

-q, --quiet

Don't show informative messages.

-m, --maintmode

Enables the maintainer mode, that is the program invocation is effectuated

automatically by a maintainer script. This switch should not be used by end users.

-p, --purge

When disabling a module, purge all traces of the module in the internal state data base.

## EXIT STATUS

a2enconf and a2disconf exit with status 0 if all configurations are processed successfully, 1 if errors occur, 2 if an invalid option was used.

## EXAMPLES

```
a2enconf security
```

```
a2disconf charset
```

Enables Apache security directives stored in the security configuration files, and disables the charset configuration.

## FILES

```
/etc/apache2/conf-available
```

Directory with files giving information on available configuration files.

```
/etc/apache2/conf-enabled
```

Directory with links to the files in conf-available for enabled configuration files.

## SEE ALSO

apache2ctl(8), a2enmod(8), a2dismod(8).

## AUTHOR

This manual page was written by Arno Toell <debian@toell.net> for the Debian GNU/Linux distribution, as it is a Debian-specific script with the package.

14 February 2012

A2ENCONF(8)