



Rocky Enterprise Linux 9.2 Manual Pages on command 'aa-enabled.1'

C:\>man aa-enabled.1

AA-ENABLED(1) AppArmor AA-ENABLED(1)

NAME

aa-enabled - test whether AppArmor is enabled

SYNOPSIS

aa-enabled [options]

DESCRIPTION

aa-enabled is used to determine if AppArmor is enabled.

OPTIONS

aa-enabled accepts the following arguments:

-h, --help

Display a brief usage guide.

-q, --quiet

Do not output anything to stdout. This option is intended to be used by scripts that simply want to use the exit code to determine if AppArmor is enabled.

EXIT STATUS

Upon exiting, aa-enabled will set its exit status to the following values:

0 if AppArmor is enabled.

1 if AppArmor is not enabled/loaded.

2 intentionally not used as an aa-enabled exit status.

3 if the AppArmor control files aren't available under `/sys/kernel/security/`.

4 if aa-enabled doesn't have enough privileges to read the apparmor control files.

64 if any unexpected error or condition is encountered.

BUGS

If you find any bugs, please report them at
<<https://bugs.launchpad.net/apparmor/+filebug>>.

SEE ALSO

`apparmor(7)`, `apparmor.d(5)`, `aa_is_enabled(2)`, and <<https://wiki.apparmor.net>>.