



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'acpi\_listen.8'***

**C:\>man acpi\_listen.8**

acpi\_listen(8)                    System Manager's Manual                    acpi\_listen(8)

### NAME

acpi\_listen - ACPI event listener

### SYNOPSIS

acpi\_listen [options]

### DESCRIPTION

acpid is the system-wide ACPI event catcher. acpi\_listen is a simple shell-friendly tool which connects to acpid and listens for events. When an event occurs, acpi\_listen will print it on stdout.

### OPTIONS

-c, --count events

Receive up to a maximum number of ACPI events, then exit.

-s, --socketfile filename

This option changes the name of the UNIX domain socket which acpid opens.

Default is /var/run/acpid.socket.

-t, --time seconds

Listen for the specified time in seconds, before exiting.

`-v, --version`

Print version information and exit.

`-h, --help`

Show help and exit.

## FILES

`/var/run/acpid.socket`

## BUGS

There are no known bugs. To file bug reports, see AUTHORS below.

## SEE ALSO

`acpid(8)`

## AUTHORS

Ted Felix ([www.tedfelix.com](http://www.tedfelix.com))

Tim Hockin <[thockin@hockin.org](mailto:thockin@hockin.org)>

Luca Capello <[luca@pca.it](mailto:luca@pca.it)>

Nov 2003

`acpi_listen(8)`