



Rocky Enterprise Linux 9.2 Manual Pages on command 'avahi-browse-domains.1'

C:\>man avahi-browse-domains.1

avahi-browse(1) General Commands Manual avahi-browse(1)

NAME

avahi-browse - Browse for mDNS/DNS-SD services using the Avahi daemon

SYNOPSIS

avahi-browse [options] service-type

avahi-browse [options] --all

avahi-browse [options] --browse-domains

avahi-browse [options] --dump-db

avahi-browse-domains [options]

DESCRIPTION

Browse for mDNS/DNS-SD network services and browsing domains using the Avahi daemon.

OPTIONS

Specify a DNS-SD service type (e.g. `_http._tcp`) to browse for on the command line, or `-a` to browse for all available service types. Items that appear on the network are prefixed with "+", items that disappear are prefixed with "-". If `--resolve` is passed items that are resolved are prefixed with "=".

`-a` | `--all`

Browse for all service types registered on the LAN, not just the one specified on the command line.

`-D` | `--browse-domains`

Browse for browsing domains instead for services. `avahi-browse-domains` is

equivalent to `avahi-browse --browse-domains`

`-d | --domain= DOMAIN`

Browse in the specified domain. If omitted `avahi-browse` will browse in the default browsing domain (usually `.local`)

`-v | --verbose`

Enable verbose mode.

`-t | --terminate`

Terminate after dumping a more or less complete list.

`-c | --cache`

Terminate after dumping all entries available in the cache.

`-l | --ignore-local`

Ignore local services, show only remote services.

`-r | --resolve`

Automatically resolve services found.

`-f | --no-fail`

Don't fail if the daemon is not found running. Instead, wait until it appears. If it disconnects, try to reconnect.

`-p | --parsable`

Make output easily parsable for usage in scripts. If enabled fields are separated by semicolons (;), service names are escaped. It is recommended to combine this with `--no-db-lookup`.

`-k | --no-db-lookup`

Don't lookup services types in service type database.

`-b | --dump-db`

Dump the service type database (may be combined with `-k`)

`-h | --help`

Show help.

`-V | --version`

Show version information.

AUTHORS

The Avahi Developers <avahi (at) lists (dot) freedesktop (dot) org>; Avahi is available from <http://avahi.org/>

SEE ALSO

avahi-publish(1), avahi-resolve(1), avahi-daemon(8)

COMMENTS

This man page was written using xml2man(1) by Oliver Kurth.

Manuals

User

avahi-browse(1)