



Rocky Enterprise Linux 9.2 Manual Pages on command 'base32.1'

C:\>man base32.1

BASE32(1) User Commands BASE32(1)

NAME

base32 - base32 encode/decode data and print to standard output

SYNOPSIS

base32 [OPTION]... [FILE]

DESCRIPTION

Base32 encode or decode FILE, or standard input, to standard output.

With no FILE, or when FILE is -, read standard input.

Mandatory arguments to long options are mandatory for short options too.

-d, --decode

decode data

-i, --ignore-garbage

when decoding, ignore non-alphabet characters

-w, --wrap=COLS

wrap encoded lines after COLS character (default 76). Use 0 to disable line

wrapping

--help display this help and exit

--version

output version information and exit

The data are encoded as described for the base32 alphabet in RFC 4648. When decod?

ing, the input may contain newlines in addition to the bytes of the formal base32

alphabet. Use --ignore-garbage to attempt to recover from any other non-alphabet

bytes in the encoded stream.

AUTHOR

Written by Simon Josefsson.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report base32 translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<https://www.gnu.org/software/coreutils/base32>>

or available locally via: info '(coreutils) base32 invocation'

GNU coreutils 8.30

September 2019

BASE32(1)