



Rocky Enterprise Linux 9.2 Manual Pages on command 'base64.1'

C:\>man base64.1

BASE64(1) User Commands BASE64(1)

NAME

base64 - base64 encode/decode data and print to standard output

SYNOPSIS

base64 [OPTION]... [FILE]

DESCRIPTION

Base64 encode or decode FILE, or standard input, to standard output.

With no FILE, or when FILE is -, read standard input.

Mandatory arguments to long options are mandatory for short options too.

-d, --decode

decode data

-i, --ignore-garbage

when decoding, ignore non-alphabet characters

-w, --wrap=COLS

wrap encoded lines after COLS character (default 76). Use 0 to disable line

wrapping

--help display this help and exit

--version

output version information and exit

The data are encoded as described for the base64 alphabet in RFC 4648. When decod?

ing, the input may contain newlines in addition to the bytes of the formal base64

alphabet. Use --ignore-garbage to attempt to recover from any other non-alphabet

bytes in the encoded stream.

AUTHOR

Written by Simon Josefsson.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report base64 translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<https://www.gnu.org/software/coreutils/base64>>

or available locally via: info '(coreutils) base64 invocation'

GNU coreutils 8.30

September 2019

BASE64(1)