



Rocky Enterprise Linux 9.2 Manual Pages on command 'bcopy.3'

C:\>man bcopy.3

BCOPY(3) Linux Programmer's Manual BCOPY(3)

NAME

bcopy - copy byte sequence

SYNOPSIS

```
#include <strings.h>

void bcopy(const void *src, void *dest, size_t n);
```

DESCRIPTION

The `bcopy()` function copies `n` bytes from `src` to `dest`. The result is correct, even when both areas overlap.

RETURN VALUE

None.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?bcopy() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

4.3BSD. This function is deprecated (marked as LEGACY in POSIX.1-2001): use `memcpy(3)` or `memmove(3)` in new programs. Note that the first two arguments are interchanged for `memcpy(3)` and `memmove(3)`. POSIX.1-2008 removes the specification of

bcopy().

SEE ALSO

bstring(3), memccpy(3), memcpy(3), memmove(3), strcpy(3), strncpy(3)

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2017-03-13

BCOPY(3)