



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'bdflush.2'***

**C:\>man bdflush.2**

BDFLUSH(2)                      Linux Programmer's Manual                      BDFLUSH(2)

### NAME

bdflush - start, flush, or tune buffer-dirty-flush daemon

### SYNOPSIS

```
#include <sys/kdaemon.h>
```

```
int bdflush(int func, long *address);
```

```
int bdflush(int func, long data);
```

### DESCRIPTION

Note: Since Linux 2.6, this system call is deprecated and does nothing. It is likely to disappear altogether in a future kernel release. Nowadays, the task performed by bdflush() is handled by the kernel pdflush thread.

bdflush() starts, flushes, or tunes the buffer-dirty-flush daemon. Only a privileged process (one with the CAP\_SYS\_ADMIN capability) may call bdflush().

If func is negative or 0, and no daemon has been started, then bdflush() enters the daemon code and never returns.

If func is 1, some dirty buffers are written to disk.

If func is 2 or more and is even (low bit is 0), then address is the address of a long word, and the tuning parameter numbered (func-2)/2 is returned to the caller in that address.

If func is 3 or more and is odd (low bit is 1), then data is a long word, and the kernel sets tuning parameter numbered (func-3)/2 to that value.

The set of parameters, their values, and their valid ranges are defined in the

Linux kernel source file fs/buffer.c.

## RETURN VALUE

If `func` is negative or 0 and the daemon successfully starts, `bdflush()` never returns. Otherwise, the return value is 0 on success and -1 on failure, with `errno` set to indicate the error.

## ERRORS

**EBUSY** An attempt was made to enter the daemon code after another process has already entered.

**EFAULT** address points outside your accessible address space.

**EINVAL** An attempt was made to read or write an invalid parameter number, or to write an invalid value to a parameter.

**EPERM** Caller does not have the `CAP_SYS_ADMIN` capability.

## VERSIONS

Since version 2.23, glibc no longer supports this obsolete system call.

## CONFORMING TO

`bdflush()` is Linux-specific and should not be used in programs intended to be portable.

## SEE ALSO

`sync(1)`, `fsync(2)`, `sync(2)`

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.