



Rocky Enterprise Linux 9.2 Manual Pages on command 'broadwayd.1'

C:~>man *broadwayd.1*

BROADWAYD(1) User Commands BROADWAYD(1)

NAME

broadwayd - Broadway display server

SYNOPSIS

broadwayd [--port PORT] [--address ADDRESS] [--unixsocket ADDRESS] [:DISPLAY]

DESCRIPTION

broadwayd is a display server for the Broadway GDK backend. It allows multiple GTK+ applications to display their windows in the same web browser, by connecting to `broadwayd`.

When using `broadwayd`, specify the display number to use, prefixed with a colon, similar to X. The default display number is 0.

```
broadwayd :5
```

Then point your web browser at `http://127.0.0.1:8085`. Start your applications like this:

```
GDK_BACKEND=broadway BROADWAY_DISPLAY=:5 gtk3-demo
```

You can add password protection for your session by creating a file in `$XDG_CONFIG_HOME/broadway.passwd` or `$HOME/.config/broadway.passwd` with a `crypt(3)` style password hash. A simple way to generate it is with `openssl`:

```
openssl passwd -1 > ~/.config/broadway.passwd
```

OPTIONS

`--port`

Use `PORT` as the HTTP port, instead of the default `8080 + (DISPLAY - 1)`.

--address

Use ADDRESS as the HTTP address, instead of the default http://127.0.0.1:PORT.

--unixsocket

Use ADDRESS as the unix domain socket address. This option overrides --address and --port. It is available only on Unix-like systems.

GTK+

BROADWAYD(1)