



Rocky Enterprise Linux 9.2 Manual Pages on command 'bundle-gem2.7.1'

C:\>man bundle-gem2.7.1

BUNDLE-GEM(1)

BUNDLE-GEM(1)

NAME

bundle-gem - Generate a project skeleton for creating a rubygem

SYNOPSIS

bundle gem GEM_NAME OPTIONS

DESCRIPTION

Generates a directory named GEM_NAME with a Rakefile, GEM_NAME.gemspec, and other supporting files and directories that can be used to develop a rubygem with that name.

Run rake -T in the resulting project for a list of Rake tasks that can be used to test and publish the gem to rubygems.org.

The generated project skeleton can be customized with OPTIONS, as explained below.

Note that these options can also be specified via Bundler's global configuration file using the following names:

? gem.coc

? gem.mit

? gem.test

OPTIONS

--exe or -b or --bin

Specify that Bundler should create a binary executable (as exe/GEM_NAME) in the generated rubygem project. This binary will also be added to the GEM_NAME.gemspec manifest. This behavior is disabled by default.

--no-exe

Do not create a binary (overrides --exe specified in the global config).

--coc Add a CODE_OF_CONDUCT.md file to the root of the generated project. If this

option is unspecified, an interactive prompt will be displayed and the an?

swer will be saved in Bundler's global config for future bundle gem use.

--no-coc

Do not create a CODE_OF_CONDUCT.md (overrides --coc specified in the global config).

--ext Add boilerplate for C extension code to the generated project. This behavior

is disabled by default.

--no-ext

Do not add C extension code (overrides --ext specified in the global config).

--mit Add an MIT license to a LICENSE.txt file in the root of the generated

project. Your name from the global git config is used for the copyright

statement. If this option is unspecified, an interactive prompt will be dis?

played and the answer will be saved in Bundler's global config for future bundle gem use.

--no-mit

Do not create a LICENSE.txt (overrides --mit specified in the global config).

-t, --test=minitest, --test=rspec

Specify the test framework that Bundler should use when generating the project. Acceptable values are minitest and rspec. The GEM_NAME.gemspec will be configured and a skeleton test/spec directory will be created based on this option. If this option is unspecified, an interactive prompt will be displayed and the answer will be saved in Bundler's global config for future bundle gem use. If no option is specified, the default testing framework is RSpec.

-e, --edit[=EDITOR]

Open the resulting GEM_NAME.gemspec in EDITOR, or the default editor if not specified. The default is \$BUNDLER_EDITOR, \$VISUAL, or \$EDITOR.

? bundle config(1) bundle-config.1.html

December 2019

BUNDLE-GEM(1)