



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'chroot.8'***

**C:\>man chroot.8**

CHROOT(8)                      User Commands                      CHROOT(8)

### NAME

chroot - run command or interactive shell with special root directory

### SYNOPSIS

chroot [OPTION] NEWROOT [COMMAND [ARG]...]

chroot OPTION

### DESCRIPTION

Run COMMAND with root directory set to NEWROOT.

--groups=G\_LIST

    specify supplementary groups as g1,g2,...,gN

--userspec=USER:GROUP

    specify user and group (ID or name) to use

--skip-chdir

    do not change working directory to '/'

--help display this help and exit

--version

    output version information and exit

If no command is given, run "\$SHELL" -i' (default: '/bin/sh -i').

### AUTHOR

Written by Roland McGrath.

### REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report chroot translation bugs to <<https://translationproject.org/team/>>

## COPYRIGHT

Copyright ? 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

chroot(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/chroot>>

or available locally via: info '(coreutils) chroot invocation'

GNU coreutils 8.30

September 2019

CHROOT(8)