



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'crypt\_checksalt.3'***

**C:\>man crypt\_checksalt.3**

CRYPT\_CHECKSALT(3)      BSD Library Functions Manual      CRYPT\_CHECKSALT(3)

### NAME

crypt\_checksalt ? validate a crypt setting string

### LIBRARY

Crypt Library (libcrypt, -lcrypt)

### SYNOPSIS

```
#include <crypt.h>
```

```
int
```

```
crypt_checksalt(const char *setting);
```

### DESCRIPTION

crypt\_checksalt checks the setting string against the system configuration and reports whether the hashing method and parameters it specifies are acceptable. It is intended to be used by programs such as login(1) to determine whether the user's passphrase should be re-hashed using the currently preferred hashing method.

### RETURN VALUES

The return value is 0 if there is nothing wrong with this setting. Otherwise, it is

one of the following constants:

#### CRYPT\_SALT\_OK

setting is a fully correct setting string. This constant is guaranteed to equal 0.

#### CRYPT\_SALT\_INVALID

setting is not a valid setting string; either it specifies a hashing method that is not known to this version of libxcrypt, or it specifies invalid parameters for the method.

#### CRYPT\_SALT\_METHOD\_DISABLED (Not implemented, yet)

setting specifies a hashing method that is no longer allowed to be used at all; crypt will fail if passed this setting. Manual intervention will be required to reactivate the user's account.

#### CRYPT\_SALT\_METHOD\_LEGACY (Not implemented, yet)

setting specifies a hashing method that is no longer considered strong enough for use with new passphrases. crypt will still authenticate a passphrase against this setting, but if authentication succeeds, the passphrase should be re-hashed using the currently preferred method.

#### CRYPT\_SALT\_TOO\_CHEAP (Not implemented, yet)

setting specifies cost parameters that are considered too cheap for use with new passphrases. crypt will still authenticate a passphrase against this setting, but if authentication succeeds, the passphrase should be re-hashed using the currently preferred method.

#### FEATURE TEST MACROS

<crypt.h> will define the macro CRYPT\_CHECKSALT\_AVAILABLE if crypt\_checksalt is available in the current version of libxcrypt.

Since full configurability is not yet implemented, the current implementation will only ever return CRYPT\_SALT\_OK (0) or CRYPT\_SALT\_INVALID when invoked.

## PORTABILITY NOTES

The function crypt\_checksalt is not part of any standard. It was added to libxcrypt in version 4.3.0.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?crypt\_checksalt ? Thread safety ? MT-Safe ?

??

## SEE ALSO

crypt(3), crypt\_gensalt(3), crypt(5)