



Rocky Enterprise Linux 9.2 Manual Pages on command 'ctrlaltdel.8'

C:\>man ctrlaltdel.8

CTRLALTDDEL(8) System Administration CTRLALTDDEL(8)

NAME

ctrlaltdel - set the function of the Ctrl-Alt-Del combination

SYNOPSIS

ctrlaltdel hard|soft

DESCRIPTION

Based on examination of the linux/kernel/reboot.c code, it is clear that there are two supported functions that the Ctrl-Alt-Del sequence can perform.

hard Immediately reboot the computer without calling sync(2) and without any other preparation. This is the default.

soft Make the kernel send the SIGINT (interrupt) signal to the init process (this is always the process with PID 1). If this option is used, the init(8) program must support this feature. Since there are now several init(8) programs in the Linux community, please consult the documentation for the version that you are currently using.

When the command is run without any argument, it will display the current setting.

The function of ctrlaltdel is usually set in the /etc/rc.local file.

OPTIONS

-V, --version

Display version information and exit.

-h, --help

Display help text and exit.

FILES

`/etc/rc.local`

SEE ALSO

`init(8)`, `systemd(1)`

AUTHOR

Peter Orbaek poe@daimi.aau.dk

AVAILABILITY

The `ctrlaltdel` command is part of the `util-linux` package and is available from Linux Kernel Archive <https://www.kernel.org/pub/linux/utils/util-linux/>.

`util-linux`

October 2015

`CTRLALTDDEL(8)`