



Rocky Enterprise Linux 9.2 Manual Pages on command 'deb-changelog.5'

C:\>man deb-changelog.5

deb-changelog(5) dpkg suite deb-changelog(5)

NAME

deb-changelog - dpkg source packages' changelog file format

SYNOPSIS

changelog

DESCRIPTION

Changes in the packaged version of a project are explained in the changelog file `debian/changelog`. This includes modifications made in the source package compared to the upstream one as well as other changes and updates to the package.

The format of the `debian/changelog` allows the package building tools to discover which version of the package is being built and find out other release-specific information.

That format is a series of entries like this:

package (version) distributions; metadata

[optional blank line(s), stripped]

* change-details

more-change-details

[blank line(s), included in output of `dpkg-parsechangelog(1)`]

* even-more-change-details

[optional blank line(s), stripped]

-- maintainer-name <email-address> date

package and version are the source package name and version number.

distributions lists one or more space-separated distributions where this version should be installed when it is uploaded; it is copied to the Distribution field in the .changes file.

metadata is a comma-separated list of keyword=value items. The only keywords currently supported by dpkg are urgency and binary-only. urgency's value is used for the Urgency field in the .changes file for the upload. binary-only with a yes value, is used to denote that this changelog entry is for a binary-only non-maintainer upload (an automatic binary rebuild with the only change being the changelog entry).

The change details may in fact be any series of lines starting with at least two spaces, but conventionally each change starts with an asterisk and a separating space and continuation lines are indented so as to bring them in line with the start of the text above. Blank lines may be used here to separate groups of changes, if desired.

If this upload resolves bugs recorded in the distribution bug tracking system, they may be automatically closed on the inclusion of this package into the distribution archive by including the string:

Closes: Bug#nnnnn

in the change details (the exact Perl regular expression is `/closes:\s*(?:bug)?\#\s?\d+(?:,\s*(?:bug)?\#\s?\d+)*\s*/i`). This information is conveyed via the Closes field in the .changes file.

The maintainer name and email address used in the changelog should be the details of the person who prepared this release of the package. They are not necessarily those of the uploader or usual package maintainer. The information here will be copied to the Changed-By field in the .changes file, and then later might be used to send an acknowledgement when the upload has been installed in the distribution archive.

The date has the following format (compatible and with the same semantics of RFC2822 and RFC5322, or what `?date -R?` generates):

day-of-week, dd month yyyy hh:mm:ss +zzzz

where:

day-of-week

Is one of: Mon, Tue, Wed, Thu, Fri, Sat, Sun.

dd Is a one- or two-digit day of the month (01-31).

month Is one of: Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, Dec.

yyyy Is the four-digit year (e.g. 2010).

hh Is the two-digit hour (00-23).

mm Is the two-digit minutes (00-59).

ss Is the two-digit seconds (00-60).

[+-]zzzz

Is the time zone offset from Coordinated Universal Time (UTC). ?+?

indicates that the time is ahead of (i.e., east of) UTC and ?-? indicates

that the time is behind (i.e., west of) UTC. The first two digits indicate

the hour difference from UTC and the last two digits indicate the number of

additional minutes difference from UTC. The last two digits must be in the

range 00-59.

The first ?title? line with the package name must start at the left hand margin.

The ?trailer? line with the maintainer and date details must be preceded by exactly one space. The maintainer details and the date must be separated by exactly two spaces.

Any line that consists entirely (i.e., no leading whitespace) of # or /* */ style comments or RCS keywords.

Vim modelines or Emacs local variables, and ancient changelog entries with other formats at the end of the file should be accepted and preserved on output, but their contents might be otherwise ignored and parsing stopped at that point.

The entire changelog must be encoded in UTF-8.

FILES

debian/changelog

EXAMPLES

```
dpkg (1.17.18) unstable; urgency=low
```

```
[ Guillem Jover ]
```

```
* Handle empty minimum versions when initializing dependency versions,  
as the code is mapping the minimum version 0 to "" to avoid outputting  
useless versions. Regression introduced in dpkg 1.17.17. Closes: #764929
```

```
[ Updated programs translations ]
```

```
* Catalan (Guillem Jover).
```

[Updated dselect translations]

* Catalan (Guillem Jover).

* German (Sven Joachim).

-- Guillem Jover <guillem@debian.org> Sun, 12 Oct 2014 15:47:44 +0200

SEE ALSO

deb-version(7), deb-changes(5), dpkg-parsechangelog(1).

1.19.7

2022-05-25

deb-changelog(5)