



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'deluser.conf.5'***

**C:\>man deluser.conf.5**

deluser.conf(5)                      File Formats Manual                      deluser.conf(5)

### NAME

/etc/deluser.conf - configuration file for deluser(8) and delgroup(8).

### DESCRIPTION

The file /etc/deluser.conf contains defaults for the programs deluser(8) and delgroup(8). Each option takes the form option = value. Double or single quotes are allowed around the value. Comment lines must have a hash sign (#) at the beginning of the line.

deluser(8) and delgroup(8) also read /etc/adduser.conf, see adduser.conf(5); settings in deluser.conf may overwrite settings made in adduser.conf.

The valid configuration options are:

#### REMOVE\_HOME

Removes the home directory and mail spool of the user to be removed. Value may be 0 (don't delete) or 1 (do delete).

#### REMOVE\_ALL\_FILES

Removes all files on the system owned by the user to be removed. If this

option is activated REMOVE\_HOME has no effect. Values may be 0 or 1.

BACKUP If REMOVE\_HOME or REMOVE\_ALL\_FILES is activated all files are backed up before they are removed. The backup file that is created defaults to user? name.tar(.gz|.bz2) in the directory specified by the BACKUP\_TO option. The compression method is chosen to the best that is available. Values may be 0 or 1.

#### BACKUP\_TO

If BACKUP is activated, BACKUP\_TO specifies the directory the backup is written to. Default is the current directory.

#### NO\_DEL\_PATHS

A list of regular expressions, space separated. All files to be deleted in course of deleting home directories or deleting files owned by the user to be deleted are checked against each of these regular expressions. If a match is detected, the file is not deleted. Defaults to a list of system directories, leaving only /home.

In other words: By default only files below /home belonging to that specific user are going to be deleted.

#### ONLY\_IF\_EMPTY

Only delete a group if there are no users belonging to this group. Defaults to 0.

#### EXCLUDE\_FSTYPES

A regular expression which describes all file systems which should be excluded when looking for files of a user to be deleted. Defaults to "(proc|sysfs|usbfs|devpts|tmpfs|afs)".

#### FILES

/etc/deluser.conf

SEE ALSO

[adduser.conf\(5\)](#), [delgroup\(8\)](#), [deluser\(8\)](#)

Debian GNU/Linux

Version 3.118ubuntu2

[deluser.conf\(5\)](#)