



Rocky Enterprise Linux 9.2 Manual Pages on command 'dmmp_path_status_str.3'

C:\>man dmmp_path_status_str.3

dmmp_path_status_str(3)Device Mapper Multipath API - libdmmp Manualdmmp_path_status_str(3)

NAME

dmmp_path_status_str - Convert path status to string.

SYNOPSIS

```
const char * dmmp_path_status_str (uint32_t path_status);
```

ARGUMENTS

path_status uint32_t. Path status. When provided value is not a valid path status,
return "Invalid argument".

DESCRIPTION

Convert path status uint32_t to string (const char *):

* DMMP_PATH_STATUS_UNKNOWN -- "undef"

* DMMP_PATH_STATUS_DOWN -- "faulty"

* DMMP_PATH_STATUS_UP -- "ready"

* DMMP_PATH_STATUS_SHAKY -- "shaky"

* DMMP_PATH_STATUS_GHOST -- "ghost"

* DMMP_PATH_STATUS_PENDING -- "pending"

* DMMP_PATH_STATUS_TIMEOUT -- "timeout"

* DMMP_PATH_STATUS_REMOVED -- "removed"

* DMMP_PATH_STATUS_DELAYED -- "delayed"

RETURN

const char *. The meaning of status value.

October 2022

dmmp_path_status_str

dmmp_path_status_str(3)