



Rocky Enterprise Linux 9.2 Manual Pages on command 'docker-context-create.1'

C:\>man docker-context-create.1

DOCKER(1) Docker User Manuals DOCKER(1)

NAME

docker-context-create - Create a context

SYNOPSIS

docker context create [OPTIONS] CONTEXT

DESCRIPTION

Create a context

Docker endpoint config:

NAME	DESCRIPTION	from	Copy	named context's Docker
endpoint configuration	host	Docker endpoint on which to	connect	ca
Trust certs signed only by this CA cert		Path to TLS certificate file		
key	Path to TLS key file	skip-tls-verify	Skip	TLS certificate
validation				

Kubernetes endpoint config:

NAME	DESCRIPTION	from	Copy	named context's Kuber?
------	-------------	------	------	------------------------

netes endpoint configuration config-file Path to a Kubernetes config file
context-override Overrides the context set in the kubernetes config file name?
space-override Overrides the namespace set in the kubernetes config file

Example:

```
$ docker context create my-context --description "some description" --docker  
"host=tcp://myserver:2376,ca=~/.ca-file,cert=~/.cert-file,key=~/.key-file"
```

OPTIONS

--default-stack-orchestrator="" Default orchestrator for stack operations to
use with this context (swarm|kubernetes|all)

--description="" Description of the context

--docker=[] set the docker endpoint

--from="" create context from a named context

-h, --help[=false] help for create

--kubernetes=[] set the kubernetes endpoint

SEE ALSO

[docker-context\(1\)](#)