



Rocky Enterprise Linux 9.2 Manual Pages on command 'dpkg-vendor.1'

C:\>man dpkg-vendor.1

dpkg-vendor(1) dpkg suite dpkg-vendor(1)

NAME

dpkg-vendor - queries information about distribution vendors

SYNOPSIS

dpkg-vendor [option...] command

DESCRIPTION

dpkg-vendor is a tool to query information about vendors listed in /etc/dpkg/origins. /etc/dpkg/origins/default contains information about the current vendor.

COMMANDS

--is vendor

Exits with 0 if the current vendor is vendor. Otherwise exits with 1.

--derives-from vendor

Exits with 0 if the current vendor distribution is a derivative of vendor, otherwise exits with 1. It uses the Parent field to browse all ancestors of the current vendor.

--query field

Print on standard output the value of the vendor-specific field for the current vendor.

--help Show the usage message and exit.

--version

Show the version and exit.

OPTIONS

`--vendor vendor`

Assumes the current vendor is `vendor` instead of discovering it with the `DEB_VENDOR` environment variable or `/etc/dpkg/origins/default`.

ENVIRONMENT

`DEB_VENDOR`

This setting defines the current vendor. If not set, it will discover the current vendor by reading `/etc/dpkg/origins/default`.

`DPKG_COLORS`

Sets the color mode (since `dpkg 1.18.5`). The currently accepted values are: `auto` (default), `always` and `never`.

`DPKG-NLS`

If set, it will be used to decide whether to activate Native Language Support, also known as internationalization (or `i18n`) support (since `dpkg 1.19.0`). The accepted values are: `0` and `1` (default).

SEE ALSO

`deb-origin(5)`.

1.19.7

2022-05-25

`dpkg-vendor(1)`