



Rocky Enterprise Linux 9.2 Manual Pages on command 'env.1'

C:~>man env.1

ENV(1) User Commands ENV(1)

NAME

env - run a program in a modified environment

SYNOPSIS

env [OPTION]... [-] [NAME=VALUE]... [COMMAND [ARG]...]

DESCRIPTION

Set each NAME to VALUE in the environment and run COMMAND.

Mandatory arguments to long options are mandatory for short options too.

-i, --ignore-environment

start with an empty environment

-0, --null

end each output line with NUL, not newline

-u, --unset=NAME

remove variable from the environment

-C, --chdir=DIR

change working directory to DIR

-S, --split-string=S

process and split S into separate arguments; used to pass multiple arguments

on shebang lines

-v, --debug

print verbose information for each processing step

--help display this help and exit

--version

output version information and exit

A mere - implies -i. If no COMMAND, print the resulting environment.

OPTIONS

-S/--split-string usage in scripts

The -S option allows specifying multiple parameters in a script. Running a script named 1.pl containing the following first line:

```
#!/usr/bin/env -S perl -w -T
```

Will execute perl -w -T 1.pl .

Without the '-S' parameter the script will likely fail with:

```
/usr/bin/env: 'perl -w -T': No such file or directory
```

See the full documentation for more details.

AUTHOR

Written by Richard Mlynarik, David MacKenzie, and Assaf Gordon.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report env translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: <<https://www.gnu.org/software/coreutils/env>>

or available locally via: info '(coreutils) env invocation'

GNU coreutils 8.30

September 2019

ENV(1)