



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'envsubst.1'***

**C:\>man envsubst.1**

ENVSUBST(1) GNU ENVSUBST(1)

### NAME

envsubst - substitutes environment variables in shell format strings

### SYNOPSIS

envsubst [OPTION] [SHELL-FORMAT]

### DESCRIPTION

Substitutes the values of environment variables.

Operation mode:

-v, --variables

output the variables occurring in SHELL-FORMAT

Informative output:

-h, --help

display this help and exit

-V, --version

output version information and exit

In normal operation mode, standard input is copied to standard output, with references to environment variables of the form `$VARIABLE` or `${VARIABLE}` being replaced with the corresponding values. If a SHELL-FORMAT is given, only those environment variables that are referenced in SHELL-FORMAT are substituted; otherwise all environment variables references occurring in standard input are substituted.

When `--variables` is used, standard input is ignored, and the output consists of the environment variables that are referenced in SHELL-FORMAT, one per line.

## AUTHOR

Written by Bruno Haible.

## REPORTING BUGS

Report bugs to <[bug-gnu-gettext@gnu.org](mailto:bug-gnu-gettext@gnu.org)>.

## COPYRIGHT

Copyright ? 2003-2007 Free Software Foundation, Inc. License GPLv3+: GNU GPL ver? sion 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

The full documentation for envsubst is maintained as a Texinfo manual. If the info and envsubst programs are properly installed at your site, the command

```
info envsubst
```

should give you access to the complete manual.

GNU gettext-runtime 0.19.8.1

June 2016

ENVSUBST(1)