



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'fc-validate.1'***

**C:\>man fc-validate.1**

FC-VALIDATE(1) FC-VALIDATE(1)

### NAME

fc-validate - validate font files

### SYNOPSIS

```
fc-validate [ -Vhv ]  
[ [ -i index ] [ --index index ] ] [ [ -l lang ] [ --lang lang ] ] [  
--verbose ] [ --version ] [ --help ] font-file...
```

### DESCRIPTION

fc-validate validates font-file(s) if each fonts satisfies the language coverage according to the orthography files in fontconfig. If --index is given, only one face of each file is validated, otherwise all faces are validated.

### OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

- i Only query face indexed index of each file.
- l Set lang as a language instead of current locale. this is used for -m.
- v Show more detailed information.
- V Show version of the program and exit.
- h Show summary of options.

font-file

Query font-file for font faces.

### RETURN CODES

fc-validate returns error code 0 for successful parsing, or 1 if any errors occurred or if at least one font face could not be opened.

#### AUTHOR

This manual page was updated by Akira TAGOH <akira@tagoh.org>.

Sep 10, 2012

FC-VALIDATE(1)