



Rocky Enterprise Linux 9.2 Manual Pages on command 'fdformat.8'

C:\>man fdformat.8

FDFORMAT(8) System Administration FDFORMAT(8)

NAME

fdformat - low-level format a floppy disk

SYNOPSIS

fdformat [options] device

DESCRIPTION

fdformat does a low-level format on a floppy disk. device is usually one of the following (for floppy devices the major = 2, and the minor is shown for informational purposes only):

- /dev/fd0d360 (minor = 4)
- /dev/fd0h1200 (minor = 8)
- /dev/fd0D360 (minor = 12)
- /dev/fd0H360 (minor = 12)
- /dev/fd0D720 (minor = 16)
- /dev/fd0H720 (minor = 16)
- /dev/fd0h360 (minor = 20)
- /dev/fd0h720 (minor = 24)
- /dev/fd0H1440 (minor = 28)
- /dev/fd1d360 (minor = 5)
- /dev/fd1h1200 (minor = 9)
- /dev/fd1D360 (minor = 13)
- /dev/fd1H360 (minor = 13)

/dev/fd1D720 (minor = 17)

/dev/fd1H720 (minor = 17)

/dev/fd1h360 (minor = 21)

/dev/fd1h720 (minor = 25)

/dev/fd1H1440 (minor = 29)

The generic floppy devices, /dev/fd0 and /dev/fd1, will fail to work with fdformat when a non-standard format is being used, or if the format has not been autode? tected earlier. In this case, use setfdprm(8) to load the disk parameters.

OPTIONS

-f, --from N

Start at the track N (default is 0).

-t, --to N

Stop at the track N.

-r, --repair N

Try to repair tracks failed during the verification (max N retries).

-n, --no-verify

Skip the verification that is normally performed after the formatting.

-V, --version

Display version information and exit.

-h, --help

Display help text and exit.

SEE ALSO

fd(4), emkfs(8), mkfs(8), setfdprm(8)

AUTHOR

Werner Almesberger (almesber@nessie.cs.id.ethz.ch)

AVAILABILITY

The fdformat command is part of the util-linux package and is available from <https://www.kernel.org/pub/linux/utils/util-linux/>.