



Rocky Enterprise Linux 9.2 Manual Pages on command 'fincore.1'

C:\>man fincore.1

FINCORE(1) User Commands FINCORE(1)

NAME

fincore - count pages of file contents in core

SYNOPSIS

fincore [options] file ...

DESCRIPTION

fincore counts pages of file contents being resident in memory (in core), and reports the numbers. If an error occurs during counting, then an error message is printed to the stderr and fincore continues processing the rest of files listed in a command line.

The default output is subject to change. So whenever possible, you should avoid using default outputs in your scripts. Always explicitly define expected columns by using --output columns-list in environments where a stable output is required.

OPTIONS

-n, --noheadings

Do not print a header line in status output.

-b, --bytes

Print the SIZE column in bytes rather than in a human-readable format.

-o, --output list

Define output columns. See the --help output to get a list of the currently supported columns. The default list of columns may be extended if list is specified in the format +list.

-r, --raw

Produce output in raw format. All potentially unsafe characters are hex-escaped (\x<code>).

-J, --json

Use JSON output format.

-V, --version

Display version information and exit.

-h, --help

Display help text and exit.

AUTHORS

Masatake YAMATO <yamato@redhat.com>

SEE ALSO

mincore(2), getpagesize(2), getconf(1)

AVAILABILITY

The `findcore` command is part of the `util-linux` package and is available from Linux Kernel Archive <<https://www.kernel.org/pub/linux/utils/util-linux/>>.

util-linux

March 2017

FINCORE(1)