



Rocky Enterprise Linux 9.2 Manual Pages on command 'fmal.3'

C:\>man fmal.3

FMA(3) Linux Programmer's Manual FMA(3)

NAME

fma, fmaf, fmal - floating-point multiply and add

SYNOPSIS

```
#include <math.h>
```

```
double fma(double x, double y, double z);
```

```
float fmaf(float x, float y, float z);
```

```
long double fmal(long double x, long double y, long double z);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

```
fma(), fmaf(), fmal():
```

```
  _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

These functions compute $x * y + z$. The result is rounded as one ternary operation according to the current rounding mode (see `fenv(3)`).

RETURN VALUE

These functions return the value of $x * y + z$, rounded as one ternary operation.

If x or y is a NaN, a NaN is returned.

If x times y is an exact infinity, and z is an infinity with the opposite sign, a domain error occurs, and a NaN is returned.

If one of x or y is an infinity, the other is 0, and z is not a NaN, a domain error occurs, and a NaN is returned.

If one of x or y is an infinity, and the other is 0, and z is a NaN, a domain error occurs, and a NaN is returned.

If x times y is not an infinity times zero (or vice versa), and z is a NaN, a NaN is returned.

If the result overflows, a range error occurs, and an infinity with the correct sign is returned.

If the result underflows, a range error occurs, and a signed 0 is returned.

ERRORS

See `math_error(7)` for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: $x * y + z$, or $x * y$ is invalid and z is not a NaN

An invalid floating-point exception (`FE_INVALID`) is raised.

Range error: result overflow

An overflow floating-point exception (`FE_OVERFLOW`) is raised.

Range error: result underflow

An underflow floating-point exception (`FE_UNDERFLOW`) is raised.

These functions do not set `errno`.

VERSIONS

These functions first appeared in `glibc` in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`fma()`, `fmaf()`, `fmal()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

SEE ALSO

`remainder(3)`, `remquo(3)`

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of

the project, information about reporting bugs, and the latest version of this page,
can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

FMA(3)