



Rocky Enterprise Linux 9.2 Manual Pages on command 'gdk-pixbuf-query-loaders.1'

C:\>man gdk-pixbuf-query-loaders.1

GDK-PIXBUF-QUERY-(1) User Commands GDK-PIXBUF-QUERY-(1)

NAME

gdk-pixbuf-query-loaders - GdkPixbuf loader registration utility

SYNOPSIS

gdk-pixbuf-query-loaders [--update-cache] [MODULE...]

DESCRIPTION

gdk-pixbuf-query-loaders collects information about loadable modules for gdk-pixbuf and writes it to the default cache file location, or to stdout.

If called without arguments, it looks for modules in the gdk-pixbuf loader directory.

If called with arguments, it looks for the specified modules. The arguments may be absolute or relative paths.

Normally, the output of gdk-pixbuf-queryloaders is written to libdir/gdk-pixbuf-2.0/2.10.0/loaders.cache, where gdk-pixbuf looks for it by default. If it is written to some other location, the environment variable GDK_PIXBUF_MODULE_FILE can be set to point gdk-pixbuf at the file.

OPTIONS

--update-cache

Write the output to the default cache location instead of stdout

ENVIRONMENT

The environment variable GDK_PIXBUF_MODULEDIR can be used to specify a different loader directory. The default gdk-pixbuf loader directory is

libdir/gdk-pixbuf-2.0/version/loaders.

gdk-pixbuf

GDK-PIXBUF-QUERY-(1)