



## **Rocky Enterprise Linux 9.2 Manual Pages on command 'getservbyname\_r.3'**

**C:\>man getservbyname\_r.3**

GETSERVENT\_R(3)                   Linux Programmer's Manual                   GETSERVENT\_R(3)

### NAME

getservent\_r, getservbyname\_r, getservbyport\_r - get service entry (reentrant)

### SYNOPSIS

```
#include <netdb.h>
```

```
int getservent_r(struct servent *result_buf, char *buf,  
                 size_t buflen, struct servent **result);
```

```
int getservbyname_r(const char *name, const char *proto,  
                   struct servent *result_buf, char *buf,  
                   size_t buflen, struct servent **result);
```

```
int getservbyport_r(int port, const char *proto,  
                   struct servent *result_buf, char *buf,  
                   size_t buflen, struct servent **result);
```

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

getservent\_r(), getservbyname\_r(), getservbyport\_r():

Since glibc 2.19:

```
  _DEFAULT_SOURCE
```

Glibc 2.19 and earlier:

```
  _BSD_SOURCE || _SVID_SOURCE
```

### DESCRIPTION

The getservent\_r(), getservbyname\_r(), and getservbyport\_r() functions are the reentrant equivalents of, respectively, getservent(3), getservbyname(3), and get?

servbyport(3). They differ in the way that the servent structure is returned, and in the function calling signature and return value. This manual page describes just the differences from the nonreentrant functions.

Instead of returning a pointer to a statically allocated servent structure as the function result, these functions copy the structure into the location pointed to by result\_buf.

The buf array is used to store the string fields pointed to by the returned servent structure. (The nonreentrant functions allocate these strings in static storage.)

The size of this array is specified in buflen. If buf is too small, the call fails with the error ERANGE, and the caller must try again with a larger buffer. (A buffer of length 1024 bytes should be sufficient for most applications.)

If the function call successfully obtains a service record, then \*result is set pointing to result\_buf; otherwise, \*result is set to NULL.

#### RETURN VALUE

On success, these functions return 0. On error, they return one of the positive error numbers listed in errors.

On error, record not found (getservbyname\_r(), getservbyport\_r()), or end of input (getservent\_r()) result is set to NULL.

#### ERRORS

ENOENT (getservent\_r()) No more records in database.

ERANGE buf is too small. Try again with a larger buffer (and increased buflen).

#### ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?getservent\_r(), ? Thread safety ? MT-Safe locale ?

?getservbyname\_r(), ? ? ?

?getservbyport\_r() ? ? ?

??

#### CONFORMING TO

These functions are GNU extensions. Functions with similar names exist on some other systems, though typically with different calling signatures.

## EXAMPLE

The program below uses `getservbyport_r()` to retrieve the service record for the port and protocol named in its first command-line argument. If a third (integer) command-line argument is supplied, it is used as the initial value for `buflen`; if `getservbyport_r()` fails with the error `ERANGE`, the program retries with larger buffer sizes. The following shell session shows a couple of sample runs:

```
$ ./a.out 7 tcp 1
ERANGE! Retrying with larger buffer
getservbyport_r() returned: 0 (success) (buflen=87)
s_name=echo; s_proto=tcp; s_port=7; aliases=
$ ./a.out 77777 tcp
getservbyport_r() returned: 0 (success) (buflen=1024)
Call failed/record not found
```

### Program source

```
#define _GNU_SOURCE
#include <ctype.h>
#include <netdb.h>
#include <stdlib.h>
#include <stdio.h>
#include <errno.h>
#include <string.h>
#define MAX_BUF 10000
int
main(int argc, char *argv[])
{
    int buflen, erange_cnt, port, s;
    struct servent result_buf;
    struct servent *result;
    char buf[MAX_BUF];
    char *protop;
    char **p;
    if (argc < 3) {
        printf("Usage: %s port-num proto-name [buflen]\n", argv[0]);
```

```

    exit(EXIT_FAILURE);
}
port = htons(atoi(argv[1]));
protop = (strcmp(argv[2], "null") == 0 ||
    strcmp(argv[2], "NULL") == 0) ? NULL : argv[2];
buflen = 1024;
if (argc > 3)
    buflen = atoi(argv[3]);
if (buflen > MAX_BUF) {
    printf("Exceeded buffer limit (%d)\n", MAX_BUF);
    exit(EXIT_FAILURE);
}
erange_cnt = 0;
do {
    s = getservbyport_r(port, protop, &result_buf,
        buf, buflen, &result);
    if (s == ERANGE) {
        if (erange_cnt == 0)
            printf("ERANGE! Retrying with larger buffer\n");
        erange_cnt++;
        /* Increment a byte at a time so we can see exactly
        what size buffer was required */
        buflen++;
        if (buflen > MAX_BUF) {
            printf("Exceeded buffer limit (%d)\n", MAX_BUF);
            exit(EXIT_FAILURE);
        }
    }
} while (s == ERANGE);
printf("getservbyport_r() returned: %s (buflen=%d)\n",
    (s == 0) ? "0 (success)" : (s == ENOENT) ? "ENOENT" :
    strerror(s), buflen);
if (s != 0 || result == NULL) {

```

```
    printf("Call failed/record not found\n");
    exit(EXIT_FAILURE);
}
printf("s_name=%s; s_proto=%s; s_port=%d; aliases=",
       result_buf.s_name, result_buf.s_proto,
       ntohs(result_buf.s_port));
for (p = result_buf.s_aliases; *p != NULL; p++)
    printf("%s ", *p);
printf("\n");
exit(EXIT_SUCCESS);
}
```

#### SEE ALSO

getservent(3), services(5)

#### COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2019-03-06

GETSERVENT\_R(3)