



Rocky Enterprise Linux 9.2 Manual Pages on command 'gettext.1'

C:\>man gettext.1

GETTEXT(1) GNU GETTEXT(1)

NAME

gettext - translate message

SYNOPSIS

gettext [OPTION] [[TEXTDOMAIN] MSGID]

gettext [OPTION] -s [MSGID]...

DESCRIPTION

The gettext program translates a natural language message into the user's language, by looking up the translation in a message catalog.

Display native language translation of a textual message.

-d, --domain=TEXTDOMAIN

retrieve translated messages from TEXTDOMAIN

-e enable expansion of some escape sequences

-E (ignored for compatibility)

-h, --help

display this help and exit

-n suppress trailing newline

-V, --version

display version information and exit

[TEXTDOMAIN] MSGID

retrieve translated message corresponding to MSGID from TEXTDOMAIN

If the TEXTDOMAIN parameter is not given, the domain is determined from the `envi?`

ronment variable TEXTDOMAIN. If the message catalog is not found in the regular directory, another location can be specified with the environment variable TEXTDO? MAINDIR. When used with the -s option the program behaves like the 'echo' command. But it does not simply copy its arguments to stdout. Instead those messages found in the selected catalog are translated. Standard search directory: /usr/share/lo?

cale

AUTHOR

Written by Ulrich Drepper.

REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

COPYRIGHT

Copyright ? 1995-1997, 2000-2007 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for gettext is maintained as a Texinfo manual. If the info and gettext programs are properly installed at your site, the command

info gettext

should give you access to the complete manual.

GNU gettext-runtime 0.19.8.1

June 2016

GETTEXT(1)