



Rocky Enterprise Linux 9.2 Manual Pages on command 'getutid_r.3'

C:\>man getutid_r.3

GETUTENT(3) Linux Programmer's Manual GETUTENT(3)

NAME

getutent, getutid, getutline, pututline, setutent, endutent, utmpname - access utmp file entries

SYNOPSIS

```
#include <utmp.h>

struct utmp *getutent(void);

struct utmp *getutid(const struct utmp *ut);

struct utmp *getutline(const struct utmp *ut);

struct utmp *pututline(const struct utmp *ut);

void setutent(void);

void endutent(void);

int utmpname(const char *file);
```

DESCRIPTION

New applications should use the POSIX.1-specified "utmpx" versions of these functions; see CONFORMING TO.

utmpname() sets the name of the utmp-format file for the other utmp functions to access. If utmpname() is not used to set the filename before the other functions are used, they assume _PATH_UTMP, as defined in <paths.h>.

setutent() rewinds the file pointer to the beginning of the utmp file. It is generally a good idea to call it before any of the other functions.

endutent() closes the utmp file. It should be called when the user code is done

accessing the file with the other functions.

`getutent()` reads a line from the current file position in the `utmp` file. It re-

turns a pointer to a structure containing the fields of the line. The definition

of this structure is shown in `utmp(5)`.

`getutid()` searches forward from the current file position in the `utmp` file based

upon `ut`. If `ut->ut_type` is one of `RUN_LVL`, `BOOT_TIME`, `NEW_TIME`, or `OLD_TIME`, `getu?`

`tid()` will find the first entry whose `ut_type` field matches `ut->ut_type`. If

`ut->ut_type` is one of `INIT_PROCESS`, `LOGIN_PROCESS`, `USER_PROCESS`, or `DEAD_PROCESS`,

`getutid()` will find the first entry whose `ut_id` field matches `ut->ut_id`.

`getutline()` searches forward from the current file position in the `utmp` file. It

scans entries whose `ut_type` is `USER_PROCESS` or `LOGIN_PROCESS` and returns the first

one whose `ut_line` field matches `ut->ut_line`.

`pututline()` writes the `utmp` structure `ut` into the `utmp` file. It uses `getutid()` to

search for the proper place in the file to insert the new entry. If it cannot find

an appropriate slot for `ut`, `pututline()` will append the new entry to the end of the

file.

RETURN VALUE

`getutent()`, `getutid()`, and `getutline()` return a pointer to a struct `utmp` on suc?

cess, and `NULL` on failure (which includes the "record not found" case). This

struct `utmp` is allocated in static storage, and may be overwritten by subsequent

calls.

On success `pututline()` returns `ut`; on failure, it returns `NULL`.

`utmpname()` returns 0 if the new name was successfully stored, or -1 on failure.

In the event of an error, these functions `errno` set to indicate the cause.

ERRORS

`ENOMEM` Out of memory.

`ESRCH` Record not found.

`setutent()`, `pututline()`, and the `getut*()` functions can also fail for the reasons

described in `open(2)`.

FILES

`/var/run/utmp`

database of currently logged-in users

`/var/log/wtmp`

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?getutent() ? Thread safety ? MT-Unsafe init race:utent ?

? ? ? race:utentbuf sig:ALRM timer ?

??

?getutid(), ? Thread safety ? MT-Unsafe init race:utent ?

?getutline() ? ? sig:ALRM timer ?

??

?pututline() ? Thread safety ? MT-Unsafe race:utent ?

? ? ? sig:ALRM timer ?

??

?setutent(), ? Thread safety ? MT-Unsafe race:utent ?

?endutent(), ? ? ?

?utmpname() ? ? ?

??

In the above table, utent in race:utent signifies that if any of the functions setutent(), getutent(), getutid(), getutline(), pututline(), utmpname(), or endutent() are used in parallel in different threads of a program, then data races could occur.

CONFORMING TO

XPG2, SVr4.

In XPG2 and SVID 2 the function pututline() is documented to return void, and that is what it does on many systems (AIX, HP-UX). HP-UX introduces a new function _pututline() with the prototype given above for pututline().

All these functions are obsolete now on non-Linux systems. POSIX.1-2001 and POSIX.1-2008, following SUSv1, does not have any of these functions, but instead uses

```
#include <utmpx.h>
struct utmpx *getutxent(void);
```

```

struct utmpx *getutxid(const struct utmpx *);
struct utmpx *getutxline(const struct utmpx *);
struct utmpx *pututxline(const struct utmpx *);
void setutxent(void);
void endutxent(void);

```

These functions are provided by glibc, and perform the same task as their equivalents without the "x", but use struct utmpx, defined on Linux to be the same as struct utmp. For completeness, glibc also provides utmpxname(), although this function is not specified by POSIX.1.

On some other systems, the utmpx structure is a superset of the utmp structure, with additional fields, and larger versions of the existing fields, and parallel files are maintained, often /var/*/utmpx and /var/*/wtmpx.

Linux glibc on the other hand does not use a parallel utmpx file since its utmp structure is already large enough. The "x" functions listed above are just aliases for their counterparts without the "x" (e.g., getutxent() is an alias for getutent()).

NOTES

Glibc notes

The above functions are not thread-safe. Glibc adds reentrant versions

```

#include <utmp.h>

int getutent_r(struct utmp *ubuf, struct utmp **ubufp);
int getutid_r(struct utmp *ut,
              struct utmp *ubuf, struct utmp **ubufp);
int getutline_r(struct utmp *ut,
                struct utmp *ubuf, struct utmp **ubufp);

```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```

getutent_r(), getutid_r(), getutline_r():
    _GNU_SOURCE
    || /* since glibc 2.19: */ _DEFAULT_SOURCE
    || /* glibc <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE

```

These functions are GNU extensions, analogs of the functions of the same name without the _r suffix. The ubuf argument gives these functions a place to store their result. On success, they return 0, and a pointer to the result is written in

*ubufp. On error, these functions return -1. There are no utmpx equivalents of the above functions. (POSIX.1 does not specify such functions.)

EXAMPLE

The following example adds and removes a utmp record, assuming it is run from within a pseudo terminal. For usage in a real application, you should check the return values of `getpwuid(3)` and `ttyname(3)`.

```
#include <string.h>
#include <stdlib.h>
#include <pwd.h>
#include <unistd.h>
#include <utmp.h>
#include <time.h>

int
main(int argc, char *argv[])
{
    struct utmp entry;
    system("echo before adding entry::who");
    entry.ut_type = USER_PROCESS;
    entry.ut_pid = getpid();
    strcpy(entry.ut_line, ttyname(STDIN_FILENO) + strlen("/dev/"));
    /* only correct for ptys named /dev/tty[pqr][0-9a-z] */
    strcpy(entry.ut_id, ttyname(STDIN_FILENO) + strlen("/dev/tty"));
    time(&entry.ut_time);
    strcpy(entry.ut_user, getpwuid(getuid())->pw_name);
    memset(entry.ut_host, 0, UT_HOSTSIZE);
    entry.ut_addr = 0;
    setutent();
    pututline(&entry);
    system("echo after adding entry::who");
    entry.ut_type = DEAD_PROCESS;
    memset(entry.ut_line, 0, UT_LINESIZE);
    entry.ut_time = 0;
    memset(entry.ut_user, 0, UT_NAMESIZE);
```

```
setutent();  
pututline(&entry);  
system("echo after removing entry::who");  
endutent();  
exit(EXIT_SUCCESS);  
}
```

SEE ALSO

getutmp(3), utmp(5)

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2019-08-02

GETUTENT(3)