



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'git-ls-remote.1'***

**C:\>man git-ls-remote.1**

GIT-LS-REMOTE(1)                      Git Manual                      GIT-LS-REMOTE(1)

### NAME

git-ls-remote - List references in a remote repository

### SYNOPSIS

```
git ls-remote [--heads] [--tags] [--refs] [--upload-pack=<exec>]
               [-q | --quiet] [--exit-code] [--get-url] [--sort=<key>]
               [--symref] [<repository> [<refs>...]]
```

### DESCRIPTION

Displays references available in a remote repository along with the associated commit IDs.

### OPTIONS

-h, --heads, -t, --tags

Limit to only refs/heads and refs/tags, respectively. These options are not mutually exclusive; when given both, references stored in refs/heads and refs/tags are displayed.

--refs

Do not show peeled tags or pseudorefs like HEAD in the output.

-q, --quiet

Do not print remote URL to stderr.

--upload-pack=<exec>

Specify the full path of git-upload-pack on the remote host. This allows

listing references from repositories accessed via SSH and where the SSH daemon

does not use the PATH configured by the user.

`--exit-code`

Exit with status "2" when no matching refs are found in the remote repository.

Usually the command exits with status "0" to indicate it successfully talked with the remote repository, whether it found any matching refs.

`--get-url`

Expand the URL of the given remote repository taking into account any

"url.<base>.insteadOf" config setting (See `git-config(1)`) and exit without talking to the remote.

`--symref`

In addition to the object pointed by it, show the underlying ref pointed by it when showing a symbolic ref. Currently, `upload-pack` only shows the symref HEAD, so it will be the only one shown by `ls-remote`.

`--sort=<key>`

Sort based on the key given. Prefix - to sort in descending order of the value.

Supports "version:refname" or "v:refname" (tag names are treated as versions).

The "version:refname" sort order can also be affected by the "versionsort.suffix" configuration variable. See `git-for-each-ref(1)` for more sort options, but be aware keys like `committerdate` that require access to the objects themselves will not work for refs whose objects have not yet been fetched from the remote, and will give a missing object error.

`-o <option>`, `--server-option=<option>`

Transmit the given string to the server when communicating using protocol version 2. The given string must not contain a NUL or LF character. When multiple `--server-option=<option>` are given, they are all sent to the other side in the order listed on the command line.

`<repository>`

The "remote" repository to query. This parameter can be either a URL or the name of a remote (see the GIT URLS and REMOTES sections of `git-fetch(1)`).

`<refs>...`

When unspecified, all references, after filtering done with `--heads` and `--tags`, are shown. When `<refs>...` are specified, only references matching the given patterns are displayed.

## EXAMPLES

```
$ git ls-remote --tags ./.
```

```
d6602ec5194c87b0fc87103ca4d67251c76f233a refs/tags/v0.99
f25a265a342aed6041ab0cc484224d9ca54b6f41 refs/tags/v0.99.1
7ceca275d047c90c0c7d5afb13ab97efdf51bd6e refs/tags/v0.99.3
c5db5456ae3b0873fc659c19fafdde22313cc441 refs/tags/v0.99.2
0918385dbd9656cab0d1d81ba7453d49bbc16250 refs/tags/junio-gpg-pub
```

```
$ git ls-remote http://www.kernel.org/pub/scm/git/git.git master pu rc
```

```
5fe978a5381f1fbad26a80e682ddd2a401966740 refs/heads/master
c781a84b5204fb294c9ccc79f8b3baceeb32c061 refs/heads/pu
```

```
$ git remote add korg http://www.kernel.org/pub/scm/git/git.git
```

```
$ git ls-remote --tags korg v\*
```

```
d6602ec5194c87b0fc87103ca4d67251c76f233a refs/tags/v0.99
f25a265a342aed6041ab0cc484224d9ca54b6f41 refs/tags/v0.99.1
c5db5456ae3b0873fc659c19fafdde22313cc441 refs/tags/v0.99.2
7ceca275d047c90c0c7d5afb13ab97efdf51bd6e refs/tags/v0.99.3
```

## SEE ALSO

[git-check-ref-format\(1\)](#).

## GIT

Part of the [git\(1\)](#) suite

Git 2.25.1

02/08/2023

GIT-LS-REMOTE(1)