



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'groupmod.8'***

**C:\>man groupmod.8**

GROUPMOD(8)                    System Management Commands                    GROUPMOD(8)

### NAME

groupmod - modify a group definition on the system

### SYNOPSIS

groupmod [options] GROUP

### DESCRIPTION

The groupmod command modifies the definition of the specified GROUP by modifying the appropriate entry in the group database.

### OPTIONS

The options which apply to the groupmod command are:

**-g, --gid** GID

The group ID of the given GROUP will be changed to GID.

The value of GID must be a non-negative decimal integer. This value must be unique, unless the -o option is used.

Users who use the group as primary group will be updated to keep the group as their primary group.

Any files that have the old group ID and must continue to belong to GROUP, must have their group ID changed manually.

No checks will be performed with regard to the GID\_MIN, GID\_MAX, SYS\_GID\_MIN, or SYS\_GID\_MAX from /etc/login.defs.

**-h, --help**

Display help message and exit.

-n, --new-name NEW\_GROUP

The name of the group will be changed from GROUP to NEW\_GROUP name.

-o, --non-unique

When used with the -g option, allow to change the group GID to a non-unique value.

-p, --password PASSWORD

The encrypted password, as returned by crypt(3).

Note: This option is not recommended because the password (or encrypted password) will be visible by users listing the processes.

You should make sure the password respects the system's password policy.

-R, --root CHROOT\_DIR

Apply changes in the CHROOT\_DIR directory and use the configuration files from the CHROOT\_DIR directory.

-P, --prefix PREFIX\_DIR

Apply changes in the PREFIX\_DIR directory and use the configuration files from the PREFIX\_DIR directory. This option does not chroot and is intended for preparing a cross-compilation target. Some limitations: NIS and LDAP users/groups are not verified. PAM authentication is using the host files. No SELINUX support.

## CONFIGURATION

The following configuration variables in /etc/login.defs change the behavior of this tool:

MAX\_MEMBERS\_PER\_GROUP (number)

Maximum members per group entry. When the maximum is reached, a new group entry (line) is started in /etc/group (with the same name, same password, and same GID).

The default value is 0, meaning that there are no limits in the number of members in a group.

This feature (split group) permits to limit the length of lines in the group file. This is useful to make sure that lines for NIS groups are not larger than 1024 characters.

If you need to enforce such limit, you can use 25.

Note: split groups may not be supported by all tools (even in the Shadow

toolsuite). You should not use this variable unless you really need it.

## FILES

/etc/group

Group account information.

/etc/gshadow

Secure group account information.

/etc/login.defs

Shadow password suite configuration.

/etc/passwd

User account information.

## EXIT VALUES

The groupmod command exits with the following values:

0

E\_SUCCESS: success

2

E\_USAGE: invalid command syntax

3

E\_BAD\_ARG: invalid argument to option

4

E\_GID\_IN\_USE: specified group doesn't exist

6

E\_NOTFOUND: specified group doesn't exist

9

E\_NAME\_IN\_USE: group name already in use

10

E\_GRP\_UPDATE: can't update group file

11

E\_CLEANUP\_SERVICE: can't setup cleanup service

12

E\_PAM\_USERNAME: can't determine your username for use with pam

13

E\_PAM\_ERROR: pam returned an error, see syslog facility id groupmod for the PAM error message

SEE ALSO

chfn(1), chsh(1), passwd(1), gpasswd(8), groupadd(8), groupdel(8), login.defs(5),  
useradd(8), userdel(8), usermod(8).

shadow-utils 4.8.1

11/29/2022

GROUPMOD(8)