



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'grub-reboot.8'***

**C:\>man grub-reboot.8**

GRUB-REBOOT(8)            System Administration Utilities            GRUB-REBOOT(8)

### NAME

grub-reboot - set the default boot entry for GRUB, for the next boot only

### SYNOPSIS

grub-reboot [OPTION] MENU\_ENTRY

### DESCRIPTION

Set the default boot menu entry for GRUB, for the next boot only.

-h, --help

    print this message and exit

-V, --version

    print the version information and exit

--boot-directory=DIR

    expect GRUB images under the directory DIR/grub instead of the /boot/grub directory

MENU\_ENTRY is a number, a menu item title or a menu item identifier. Please note that menu items in submenus or sub-submenus require specifying the submenu components and then the menu item component. The titles should be separated using the greater-than character (>) with no extra spaces. Depending on your shell some characters including > may need escaping. More information about this is available in the GRUB Manual in the section about the 'default' command.

NOTE: In cases where GRUB cannot write to the environment block, such as when it is stored on an MDRAID or LVM device, the chosen boot menu entry will remain the de?

fault even after reboot.

## REPORTING BUGS

Report bugs to <bug-grub@gnu.org>.

## SEE ALSO

grub-set-default(8), grub-editenv(1)

The full documentation for grub-reboot is maintained as a Texinfo manual. If the info and grub-reboot programs are properly installed at your site, the command

info grub-reboot

should give you access to the complete manual.

grub-reboot 2.04-1ubuntu26.16

December 2022

GRUB-REBOOT(8)