



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ifenslave.8'***

**C:\>man ifenslave.8**

IFENSLAVE(8)                    BSD System Manager's Manual                    IFENSLAVE(8)

### NAME

ifenslave ? Attach and detach slave network devices to a bonding device.

### SYNOPSIS

ifenslave [-acdfhuvV] [--all-interfaces] [--change-active] [--detach] [--force]  
          [--help] [--usage] [--verbose] [--version] master slave ...

### DESCRIPTION

ifenslave is a tool to attach and detach slave network devices to a bonding device.

A bonding device will act like a normal Ethernet network device to the kernel, but will send out the packets via the slave devices using a simple round-robin scheduler.

This allows for simple load-balancing, identical to "channel bonding" or "trunking" techniques used in switches.

The kernel must have support for bonding devices for ifenslave to be useful.

### OPTIONS

-a, --all-interfaces

Show information about all interfaces.

-c, --change-active

Change active slave.

-d, --detach

Removes slave interfaces from the bonding device.

-f, --force

Force actions to be taken if one of the specified interfaces appears not to belong to an Ethernet device.

-h, --help

Display a help message and exit.

-u, --usage

Show usage information and exit.

-v, --verbose

Print warning and debug messages.

-V, --version

Show version information and exit.

If no options are given, the default action will be to enslave interfaces.

## EXAMPLE

The following example shows how to setup a bonding device and enslave two real Ether?

net devices to it:

```
# modprobe bonding
# ifconfig bond0 192.168.0.1 netmask 255.255.0.0
# ifenslave bond0 eth0 eth1
```

Guus Sliepen <guus@debian.org>

Debian GNU/Linux

September 3, 2023

Debian GNU/Linux