



**Rocky Enterprise Linux 9.2 Manual Pages on command 'iswprint.3'**

**C:\>man iswprint.3**

ISWPRINT(3)                      Linux Programmer's Manual                      ISWPRINT(3)

**NAME**

iswprint - test for printing wide character

**SYNOPSIS**

```
#include <wctype.h>

int iswprint(wint_t wc);
```

**DESCRIPTION**

The iswprint() function is the wide-character equivalent of the isprint(3) function. It tests whether wc is a wide character belonging to the wide-character class "print".

The wide-character class "print" is disjoint from the wide-character class "cntrl".

The wide-character class "print" contains the wide-character class "graph".

**RETURN VALUE**

The iswprint() function returns nonzero if wc is a wide character belonging to the wide-character class "print". Otherwise, it returns zero.

**ATTRIBUTES**

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?iswprint() ? Thread safety ? MT-Safe locale ?

??

## CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

## NOTES

The behavior of `iswprint()` depends on the `LC_CTYPE` category of the current locale.

## SEE ALSO

`isprint(3)`, `iswctype(3)`

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

ISWPRINT(3)