



Rocky Enterprise Linux 9.2 Manual Pages on command 'j0.3'

C:\>man j0.3

J0(3) Linux Programmer's Manual J0(3)

NAME

j0, j0f, j0l, j1, j1f, j1l, jn, jnf, jnl - Bessel functions of the first kind

SYNOPSIS

```
#include <math.h>
```

```
double j0(double x);
```

```
double j1(double x);
```

```
double jn(int n, double x);
```

```
float j0f(float x);
```

```
float j1f(float x);
```

```
float jnf(int n, float x);
```

```
long double j0l(long double x);
```

```
long double j1l(long double x);
```

```
long double jnl(int n, long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

j0(), j1(), jn():

```
  _XOPEN_SOURCE
```

```
  || /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
  || /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE
```

j0f(), j0l(), j1f(), j1l(), jnf(), jnl():

```
  _XOPEN_SOURCE >= 600
```

```
|| (_ISOC99_SOURCE && _XOPEN_SOURCE)
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE
```

DESCRIPTION

The `j0()` and `j1()` functions return Bessel functions of `x` of the first kind of orders 0 and 1, respectively. The `jn()` function returns the Bessel function of `x` of the first kind of order `n`.

The `j0f()`, `j1f()`, and `jnf()` functions are versions that take and return float values. The `j0l()`, `j1l()`, and `jnl()` functions are versions that take and return long double values.

RETURN VALUE

On success, these functions return the appropriate Bessel value of the first kind for `x`.

If `x` is a NaN, a NaN is returned.

If `x` is too large in magnitude, or the result underflows, a range error occurs, and the return value is 0.

ERRORS

See `math_error(7)` for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Range error: result underflow, or `x` is too large in magnitude
 `errno` is set to `ERANGE`.

These functions do not raise exceptions for `fetestexcept(3)`.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?`j0()`, `j0f()`, `j0l()` ? Thread safety ? MT-Safe ?

??

?`j1()`, `j1f()`, `j1l()` ? Thread safety ? MT-Safe ?

??

?`jn()`, `jnf()`, `jnl()` ? Thread safety ? MT-Safe ?

??

CONFORMING TO

The functions returning double conform to SVr4, 4.3BSD, POSIX.1-2001, and POSIX.1-2008. The others are nonstandard functions that also exist on the BSDs.

BUGS

There are errors of up to $2e-16$ in the values returned by $j_0()$, $j_1()$ and $j_n()$ for values of x between -8 and 8 .

SEE ALSO

$y_0(3)$

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

J0(3)