



Rocky Enterprise Linux 9.2 Manual Pages on command 'kpartx.8'

C:\>man kpartx.8

KPARTX(8) System Manager's Manual KPARTX(8)

NAME

kpartx - Create device maps from partition tables.

SYNOPSIS

kpartx [-a|-d|-u|-l] [-r] [-p] [-f] [-g] [-s|-n] [-v] wholedisk

DESCRIPTION

This tool, derived from util-linux' partx, reads partition tables on specified device and create device maps over partitions segments detected. It is called from hotplug upon device maps creation and deletion.

OPTIONS

- a Add partition mappings.
- d Delete partition mappings.
- u Update partition mappings.
- l List partition mappings that would be added -a.
- r Read-only partition mappings.
- p Set device name-partition number delimiter.
- f Force creation of mappings; overrides 'no_partitions' feature.
- g Force GUID partition table (GPT).
- s Sync mode (Default). Don't return until the partitions are created.
- n Nosync mode. Return before the partitions are created.
- v Operate verbosely.

EXAMPLE

To mount all the partitions in a raw disk image:

```
kpartx -av disk.img
```

This will output lines such as:

```
add map loop1p1 (254:4): 0 409597 linear 7:1 3
```

The loop1p1 is the name of a device file under /dev/mapper which you can use to access the partition, for example to fsck it:

```
fsck /dev/mapper/loop1p1
```

When you're done, you need to remove the devices:

```
kpartx -d disk.img
```

SEE ALSO

multipath(8) multipathd(8) hotplug(8)

AUTHORS

This man page was assembled By Patrick Caulfield for the Debian project.

multipath-tools was developed by Christophe Varoqui <christophe.varoqui@opensvc.com> and others.

Linux

2016-10-28

KPARTX(8)