



Rocky Enterprise Linux 9.2 Manual Pages on command 'ldrdf.1'

C:\>man ldrdf.1

LDRDF(1) Debian Manual LDRDF(1)

NAME

ldrdf - link RDOFF objects and libraries produced by rdfilib(1)

SYNOPSIS

ldrdf [-o output-file] object-file... [-llibrary...]

DESCRIPTION

ldrdf is a version of unix ld(1) (or DOS LINK) for use with RDOFF files. It is ca?

pable of linking RDOFF objects, and libraries produced with the rdfilib(1) utility.

Libraries must be specified with their path as no search is performed. Modules in

libraries are not linked to the program unless they are referred to.

OPTIONS

-o output-file

Specify an output file. The default output filename is 'aout.rdx'.

-v Increase verbosity level. Currently 4 verbosity levels are available: de?

fault (which only prints error information), normal (which prints informa?

tion about the produced object, -v), medium (which prints information about

what the program is doing, -v -v) and high (which prints all available in?

formation, -v -v -v).

-p Change alignment value to which multiple segments combigned into a single

segment should be aligned (must be either 1, 2, 4, 8, 16, 32 or 256; default

is 16).

AUTHORS

Julian Hall <jules@earthcorp.com>.

This manual page was written by Matej Vela <vela@debian.org>.

Debian Project

September 6, 1999

LDRDF(1)