



Rocky Enterprise Linux 9.2 Manual Pages on command 'log1pf.3'

C:\>man log1pf.3

LOG1P(3) Linux Programmer's Manual LOG1P(3)

NAME

log1p, log1pf, log1pl - logarithm of 1 plus argument

SYNOPSIS

```
#include <math.h>
```

```
double log1p(double x);
```

```
float log1pf(float x);
```

```
long double log1pl(long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see `feature_test_macros(7)`):

log1p():

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| _XOPEN_SOURCE >= 500
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

log1pf(), log1pl():

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

These functions return a value equivalent to

```
log(1 + x)
```

The result is computed in a way that is accurate even if the value of x is near zero.

RETURN VALUE

On success, these functions return the natural logarithm of (1 + x).

If x is a NaN, a NaN is returned.

If x is positive infinity, positive infinity is returned.

If x is -1, a pole error occurs, and the functions return -HUGE_VAL, -HUGE_VALF, or -HUGE_VALL, respectively.

If x is less than -1 (including negative infinity), a domain error occurs, and a NaN (not a number) is returned.

ERRORS

See `math_error(7)` for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: x is less than -1

`errno` is set to `EDOM` (but see `BUGS`). An invalid floating-point exception (`FE_INVALID`) is raised.

Pole error: x is -1

`errno` is set to `ERANGE` (but see `BUGS`). A divide-by-zero floating-point exception (`FE_DIVBYZERO`) is raised.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

??

?Interface ? Attribute ? Value ?

??

?log1p(), log1pf(), log1pl() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

BUGS

Before version 2.22, the glibc implementation did not set `errno` to `EDOM` when a domain error occurred.

Before version 2.22, the glibc implementation did not set `errno` to `ERANGE` when a

range error occurred.

SEE ALSO

`exp(3)`, `expm1(3)`, `log(3)`

COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

LOG1P(3)