



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'log2f.3'***

**C:\>man log2f.3**

LOG2(3)                      Linux Programmer's Manual                      LOG2(3)

### NAME

log2, log2f, log2l - base-2 logarithmic function

### SYNOPSIS

```
#include <math.h>
```

```
double log2(double x);
```

```
float log2f(float x);
```

```
long double log2l(long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see [feature\\_test\\_macros\(7\)](#)):

```
log2(), log2f(), log2l():
```

```
  _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

### DESCRIPTION

These functions return the base 2 logarithm of x.

### RETURN VALUE

On success, these functions return the base 2 logarithm of x.

For special cases, including where x is 0, 1, negative, infinity, or NaN, see

[log\(3\)](#).

### ERRORS

See [math\\_error\(7\)](#) for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see [log\(3\)](#).

## VERSIONS

These functions first appeared in glibc in version 2.1.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface            ? Attribute   ? Value   ?

??

?log2(), log2f(), log2l() ? Thread safety ? MT-Safe ?

??

## CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD.

## SEE ALSO

cbrt(3), clog2(3), log(3), log10(3), sqrt(3)

## COLOPHON

This page is part of release 5.05 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

LOG2(3)