



## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'logsave.8'***

**C:\>man logsave.8**

LOGSAVE(8)                      System Manager's Manual                      LOGSAVE(8)

### NAME

logsave - save the output of a command in a logfile

### SYNOPSIS

```
logsave [ -asv ] logfile cmd_prog [ ... ]
```

### DESCRIPTION

The logsave program will execute cmd\_prog with the specified argument(s), and save a copy of its output to logfile. If the containing directory for logfile does not exist, logsave will accumulate the output in memory until it can be written out. A copy of the output will also be written to standard output.

If cmd\_prog is a single hyphen ('-'), then instead of executing a program, logsave will take its input from standard input and save it in logfile

logsave is useful for saving the output of initial boot scripts until the /var partition is mounted, so the output can be written to /var/log.

### OPTIONS

- a This option will cause the output to be appended to logfile, instead of replacing its current contents.
- s This option will cause logsave to skip writing to the log file text which is bracketed with a control-A (ASCII 001 or Start of Header) and control-B (ASCII 002 or Start of Text). This allows progress bar information to be visible to the user on the console, while not being written to the log file.
- v This option will make logsave to be more verbose in its output to the user.

AUTHOR

Theodore Ts'o (tytso@mit.edu)

SEE ALSO

fsck(8)

E2fsprogs version 1.45.5

January 2020

LOGSAVE(8)